

# Optimize your lab's film processing efficiency with the ultra-fast, low replenishment Fuji Minilab Film Processor FP360B/FP360B AL

*Fujifilm's fast and versatile new Minilab Film Processor FP360B/FP360B AL is an excellent choice for upgrading the services of any photofinishing business. Ensuring optimum efficiency in both*

*labor and materials, the FP360B/FP360B AL offers very low replenisher needs. And it provides both high speed and high capacity, while maintaining highly stable processing quality.*

## Features

### 1 Low replenishing with stable quality

When replenishment volume begins to diminish, the quality of the rinse becomes inconsistent. The FP360B/FP360B AL, even though it is a low replenishment type, automatically replaces water lost through evaporation, thus ensuring a high quality, stable mix of replenisher.

### 2 Fast processing

While guaranteeing consistently high quality, the FP360B/FP360B AL processes a 24-exposure roll of 135 film in 10 minutes 37 seconds dry to dry.

### 3 Large-sized display

The FP360B/FP360B AL features a large display that ensures accurate and easy operation.

### 4 Automatic film loading (optional)

With an optional Automatic Film Loader, up to 20 rolls of 135 film can be loaded at one time in the Auto Loading Cassette.

## Specifications

Type:	Floor type, daylight operation
Transport System:	Leader and timing belt
Processing Speed:	467 ± 7 mm/min.
Processing Time:	10 min. 37 sec. (dry to dry)
Films:	135, 126, 110, 120, 220
Processing:	CN-16FA (exclusive Fuji chemicals)
Processing Capacity:	34 rolls/hr. (135/24 exp., 2-strip processing) 48 rolls/hr. (120, 2-strip processing)
Tank Capacity:	N1 11.5ℓ, N2 5ℓ, N3-1 5ℓ, N3-2 5ℓ, NS 3ℓ, N4-1 3ℓ, N4-2 3ℓ
Replenishment Tank:	N1 12ℓ, N2 6ℓ, N3 6ℓ, NS 14ℓ, N4 12ℓ (with simplified mixing device and solution level detector)
Waste Solution Tank:	11ℓ × 2 (with solution level detector)
Weekly Timer:	Standard
Film Collection:	Stored on hanger by leader suspension
Drying:	Auto switchover of drying air temperature by detection of film type
Power Consumption:	AC 200-240V single phase (50/60Hz), 3.3 ~ 3.9k VA
Dimensions:	690(W) × 1,431(D) × 1,604(H) mm (with Automatic Film Loader)
Weight:	195kg (280kg when operating)

\*Specifications and appearance are subject to change without notice.



FUJI PHOTO FILM CO., LTD.  
26-30, NISHIAZABU 2-CHOME,  
MINATO-KU, TOKYO 106, JAPAN