



TAKE PICTURES. FURTHER.™

Photo ©Eastman Kodak Company, 2001



DCS 760

KODAK PROFESSIONAL DCS 760 Digital Camera

The speed and range to capture great images, anywhere

Just keep shooting – and get great images, anywhere you go. With the DCS 760 Digital Camera, you can set the ISO from 80 to 400 and take a burst up to 24 frames, 1.5 every second, before writing to the PC card. Whether you use the DCS 760 for weddings, portraits, or commercial applications, you'll capture the shot you need. You'll have the most advanced digital controls and the SLR functionality of the flagship NIKON F5 Camera. All at a competitive price.

Make beautiful 16 x 20-inch prints or full-page ads with confidence. Kodak's 6-million pixel CCD (3032 x 2008) is market-proven to deliver superb images. And image review will be better than ever with the new large, bright, color LCD panel. In addition, its graphical user interface (GUI) has several innovative features, such as 1:1 focus check and a spot densitometer.

- Burst depth up to 24 frames, 1.5 every second
- ISO up to 400
- Resolution for full-page ads or 16 x 20-inch prints
- Market-proven professional digital and SLR functionality
- Larger, brighter LCD panel with unique interface
- New stand-alone software applications

The DCS 760's lightweight, rugged metal-frame body is constructed for durability and offers reliability in challenging conditions; and the removable, rechargeable battery captures 300 shots. The DCS 760 also offers composite video out and a removable IR filter; you can also get an optional, removable anti-aliasing filter.

New software is included with the camera to support studio applications – KODAK PROFESSIONAL DCS Photo Desk and KODAK PROFESSIONAL DCS Camera Manager. Or you can use third-party software. It's your choice.

DCS 760 – the professional digital camera that combines Kodak's technology, speed, and range – for great images, anywhere.

Kodak Professional

DCS 760

KODAK PROFESSIONAL DCS 760 Digital Camera



DCS 760 features

- Burst rate — 1.5 frames/second
- Burst depth — 3 to 24 images
- ISO up to 400
- Kodak's sensor technology
- Resolution for printing up to 16 x 20 inches
- Large, bright color LCD panel for image analysis
- Graphical user interface with —
 - Instant review
 - 1:1 focus check
 - Spot densitometer
 - Histogram
- New stand-alone applications — DCS Photo Desk and DCS Camera Manager
- Metal-frame NIKON F5 Camera body and familiar SLR functionality
- NiMH battery up to 300 shots or unlimited number with AC adapter
- 12-bit dynamic range
- Composite-video out—NTSC or PAL
- Internal microphone for voice recording

System recommendations

PC

- WINDOWS 2000, WINDOWS 98 SE, WINDOWS ME, or WINDOWS NT 4.0 Systems
- 233 MHz PENTIUM II Processor or greater
- 128 MB RAM minimum, 256 MB RAM recommended
- 200 MB minimum free disk space
- IEEE 1394 PCI adapter cards (if tethered without on-board 1394 port)

Macintosh systems

- MACINTOSH OS 9.04 or greater
- 300 MHz Power PC G3 or newer
- 128 MB RAM minimum, 256 MB RAM recommended
- 200 MB minimum free disk space
- IEEE 1394 PCI adapter card (if tethered without on-board 1394 port)

Specifications

- ISO Settings: 80 to 400
 - 6-megapixel CCD (3032 x 2008)
 - 18 MB finished file size
 - Bit depth: 36-bit color (12 bits per color) original capture
 - Removable, rechargeable NiMH battery
 - IR filter included
 - 1.3X focal length
 - Dual PC card slots, Type II, III
 - Optional anti-aliasing filter
 - Size: 7.6 in. (194 mm) tall, 6.2 in. (158 mm) wide, 3.4 in. (88 mm) deep
 - Weight: 4.1 lbs (1.86 kg) with battery and PC card, without lens
 - Conforms to FCC Class B, CE Mark
 - Class B Declaration, VCCI Class 2 Certified
- Specifications are subject to change without notice.

KODAK Service and Support

Our digital imaging experts can help you get the most out of your DCS 760 and optimize your efficiency. And we have a loaner program! Ask your reseller how a KODAK Care Kit can help protect your investment.

Care Kits

| | CAT No. |
|--------------------------|-----------|
| • 1-Year Gold Care Kit | 120 6085* |
| • 2-Year Gold Care Kit | 116 6883* |
| • 3-Year Gold Care Kit | 823 9386* |
| • 2-Year Silver Care Kit | 117 9969 |
| • 3-Year Silver Care Kit | 890 3312 |

*Loaners available with Gold coverage

Ordering Information

| DCS 760 Digital Camera | CAT No. |
|---|----------|
| KODAK PROFESSIONAL DCS 760 Digital Camera | 187 8461 |

| DCS 760 Accessories | CAT No. |
|--|----------|
| Anti-Aliasing Filter | 159 7186 |
| Photo Card/160 MB | 129 1335 |
| NiMH Gold Battery (6-Pack) | 821 7374 |
| NiMH Gold Battery (Single) | 178 9023 |
| Replacement IR Blocking Filter | 118 5180 |
| Replacement Battery Charger and AC Adapter Kit | 145 4438 |
| Replacement Auto DC Adapter (12-volt) | 885 4051 |
| Replacement IEEE - 1394 Cable (6-Pin) | 153 4114 |
| Canvas Camera Bag | 185 9958 |

For more information

Visit us on the web at

www.kodak.com/go/professional

For assistance in the U.S., call 1-800-23KODAK (1-800-235-6325), ext. 19. In Canada, call 1-800-465-6325, ext. 36100.

Eastman Kodak Company
343 State Street
Rochester, New York 14650 USA

www.kodak.com/go/dcs760

Kodak Professional

