



25 Frame

DIGITAL COLOR PRINTER FOR INDEXPRINT

The DCP-648 prints thumbnail size images of every frame from a roll of 135 film. A single 3 1/2" x 5", 4" x 6" or HD proportion print contains the entire roll of film. Each print includes up to 40 frame format, selected automatically according to the size of the roll. Frames and frame numbers are printed in order so it's easy to select and identify frames for enlargements or reprints. There is also a space provided so customers can title or comment on the events portrayed.

The DCP-648 can easily be attached to compatible printers or to the DCS-390 for a stand-alone index print system.



40 Frame

DCP-648 SPECIFICATIONS

Print Capacity	41 prints per hour, 86 seconds per print (4" x 6" format)
Power Requirements	AC 100V through 240V 50/60Hz
Power Consumption	350 Watts or less
Dimensions	15.6" (W) x 20" (L) x 15" (H)
Interface	SCSI-2 (Device 1) based
Input Capacity	50 Sheets (Paper Tray)
Output Capacity	20 Sheets (Paper Tray)

DCP-648 PRINT OUT SPECIFICATIONS

Print Out Capacity	Up to 40 frames on 4" x 6" or 3.5" x 5" paper
Rolls exceeding 40 frames (135H)All remaining frames will be printed on the next paper.	
Print Out Order	Starts with the lowest frame number, even if the film roll is inserted from the end
Image Magnification	Automatically switched to accommodate for 24 or 36
	film exposures on the 4" x 6" or 3.5" x 5" prints.
Frame Number	Printed on each frame at the bottom, left corner.
Density and Color Balance	. Adjustable individually through printer keyboard
Simultaneous Print OutIndex Prints™ can be made at the same time as production prints	

Specifications subject to change without notice.



