

[Home](#) > [Products](#) > [Kiosks](#) > [IP-64](#)

IP-64

The IP-64 is a compact dye-sublimation printer that delivers fast, high quality output for on-demand printing applications. Connect the IP-64 to a CT-2 or PC for an excellent entry-level digital printing solution.

Features

High-Speed Printing

The IP-64 produces a 4 x 6 print in 8 seconds. A high speed USB 2.0 connection provides a fast transfer of image data.

High Quality Prints

The IP-64 produces crisp and vivid prints with natural, continuous tones.

Easy Installation

The unit features an ultra compact footprint of approximately 1.4 square feet and is conveniently front-loading, allowing for flexible installation in almost any counter-top retail environment.

Multiple Connection Patterns

The IP-64 can be used to make prints from Noritsu's CT-2 Consumer Terminal or from a PC with Noritsu software installed. Up to two IP-64 printers can be connected to a single order input terminal.

Specifications

Printing Method (Dye Sublimation)

Resolution (334 dpi)

Print Formats (3.5" x 5", 4" x 6", 5" x 7", 6" x 8")

Interface (USB 2.0)

Dimensions (11 1/8" W x 14 1/8" H x 18 1/4" D)

Weight (Approx. 44 lb)

Printing Times

3.5" x 5" Approx. 8 seconds/print

4" x 6" Approx. 8 seconds/print

5" x 7" Approx. 15 seconds/print

6" x 8" Approx. 20 seconds/print



- Thermal printer designed for on-demand prints
- 8 seconds for a 4x6 print
- Small footprint (1.4 sq. feet)
- Fast USB 2.0 connection

CALL NORITSU

1-800-521-3686 x220

**CONTACT NORITSU
CLICK HERE**

Customer Log-In